

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (343)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru

Single ladders

Megastep L



Details

Utility value meets design: the strongest of all ZARGES ladders with high load capacity and luxurious black finish for heavy-duty use.

- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Black, wear-resistant anodised stiles.
- Wall piece at the top so that the ladder rests securely.
- Outside width: 380 mm.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty

10 years

Standards

EN 131 professional

Material	Aluminium
Coating	anodised
Connection Stile-Rung	flanged
Tread depth	60 mm
Load	max. 250 kg
Pitch rung/tread	265 mm
Producttype	Flanged single ladder with rungs
Type rung/tread	SL Step
Stile depth	73 mm

Variants

Order number	Number of rungs	Overall length	Transport dimensions	Weight	Wide crosspiece	Working height
41135	6	1.82 m	1.820 mm × 385 mm × 74 mm	3.8 kg		2.65 m
41136	8	2.38 m	2.380 mm × 385 mm × 75 mm	6.9 kg		3.15 m
41137	10	2.94 m	2.940 mm × 385 mm × 75 mm	7.5 kg		3.7 m
41138	12	3.5 m	3.500 mm × 385 mm × 75 mm	10.5 kg	0.79 m	4.25 m

Comfortstep L



Details

The ladder for maximum working comfort that is also a visual highlights.

- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.

- Outside width: 380 mm.
- Wall piece at the top so that the ladder rests securely.
- Also available as a shelf-ladder.
- Treads with plastic-cushioned front edges.
- Screwed connection between treads and stile.
- Treads and stiles made from extruded aluminium sections.
- Attractive appearance - ideal for use in offices, doctor's surgeries, law offices and sales rooms.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
Standards	EN 131 professional
Material	Aluminium
Coating	anodised
Connection Stile-Rung	bolted
Tread depth	80 mm
Load	max. 150 kg
Pitch rung/tread	250 mm
Producttype	Bolted single ladder with treads
Type rung/tread	padding on front tread edges
Stile depth	48 mm

Variants

Order number	Number of treads	Overall length	Transport dimensions	Weight	Working height
41012	6	1.87 m	1.870 mm × 382 mm × 90 mm	4.4 kg	2.75 m
41013	7	2.14 m	2.140 mm × 382 mm × 90 mm	5 kg	3 m
41014	8	2.4 m	2.410 mm × 382 mm × 90 mm	5.7 kg	3.25 m
41015	9	2.68 m	2.680 mm × 382 mm × 90 mm	6.3 kg	3.5 m
41016	10	2.95 m	2.950 mm × 382 mm × 90 mm	7 kg	3.75 m

Saferstep L



Details

The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.

- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Overall width: 420 mm.
- Also available as a shelf-ladder.
- High strength, non-twist rung/stile connections.
- Treads and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.



More Information

Warranty	10 years
----------	----------

Standards	EN 131 professional
-----------	---------------------

Material	Aluminium
----------	-----------

Coating	anodised
---------	----------

Connection Stile-Rung	flanged
-----------------------	---------

Tread depth	80 mm
-------------	-------

Load	max. 150 kg
------	-------------

Pitch rung/tread	265 mm
------------------	--------

Producttype	Single ladder with flanged treads
-------------	-----------------------------------

Type rung/tread Safer Step

Stile depth 68 mm

Variants

Order number	Number of treads	Overall length	Transport dimensions	Weight	Wide crosspiece	Working height
41356	6	1.94 m	1.930 mm × 420 mm × 73 mm	5 kg		2.8 m
41358	8	2.5 m	2.490 mm × 420 mm × 73 mm	6.5 kg		3.35 m
41360	10	3.06 m	3.050 mm × 420 mm × 73 mm	8.8 kg	0.8 m	3.85 m
41362	12	3.62 m	3.610 mm × 420 mm × 73 mm	10.3 kg	0.8 m	4.4 m
41364	14	4.18 m	4.170 mm × 420 mm × 73 mm	11.8 kg	0.89 m	4.9 m
41366	16	4.74 m	4.730 mm × 420 mm × 73 mm	13.3 kg	0.89 m	5.45 m

Seventec L



Details

The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.

- Treads 85 mm deep and with safe, non-slip serrated surfaces.
- Smooth external stile surfaces that are comfortable to hold.
- Outside width: 400 mm.

- Especially light and easy to carry.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Inside width: 360 mm.

Hints and special features

- in accordance with DIN EN 131-1, order No. 40384 includes a stabiliser bar.
- Complies with EN 131 Professional.

More Information

Warranty 10 years

Standards EN 131 professional

Material Aluminium

Coating natural

Connection Stile-Rung riveted

Tread depth 85 mm

Load max. 150 kg

Pitch rung/tread 218 mm

Producttype Riveted single ladder with treads

Type rung/tread serrated

Stile depth 87 mm

Variants

Order number	Number of treads	Overall length	Transport dimensions	Weight	Wide crosspiece	Working height
40378	8	2.08 m	2.090 mm × 400 mm × 90 mm	5.8 kg		3.05 m
40380	10	2.54 m	2.550 mm × 400 mm × 90 mm	7.2 kg		3.45 m
40382	12	2.99 m	3.010 mm × 400 mm × 90 mm	8.5 kg		3.9 m
40384	14	3.42 m	3.470 mm × 400 mm × 90 mm	11.4 kg	0.8 m	4.35 m

Stella L



Details

The flexible solution for a wide variety of uses: extra-wide ladder is comfortable to use and safe to stand on.

- Rung depth: 30 mm
- Very light but still extremely stable.
- Outside width: 490 mm.
- Also available as a shelf-ladder.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
----------	----------

Standards	EN 131 professional
-----------	---------------------

Material	Aluminium
----------	-----------

Coating	natural
---------	---------

Connection Stile-Rung	flanged
-----------------------	---------

Tread depth	30 mm
-------------	-------

Load	max. 150 kg
------	-------------

Pitch rung/tread	270 mm
------------------	--------

Producttype	Flanged single ladder with rungs
-------------	----------------------------------

Type rung/tread	serrated
-----------------	----------

Variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41511	6	1.93 m	58 mm	1.930 mm × approx. 500 mm × 60 mm	3.7 kg		2.8 m
41512	8	2.49 m	58 mm	2.480 mm × approx. 500 mm × 60 mm	4.7 kg		3.35 m
41513	10	3.05 m	58 mm	3.040 mm × approx. 500 mm × 60 mm	7.2 kg	0.8 m	3.9 m
41514	12	3.61 m	58 mm	3.600 mm × approx. 500 mm × 60 mm	8.1 kg	0.89 m	4.4 m
41515	14	4.17 m	62 mm	4.160 mm × approx. 500 mm × 65 mm	9.3 kg	0.99 m	4.95 m
41516	16	4.73 m	68 mm	4.720 mm × approx. 500 mm × 70 mm	10.5 kg	0.99 m	5.5 m
41510	18	5.29 m	73 mm	5.300 mm × approx. 500 mm × 75 mm	11.9 kg	1.09 m	6.05 m
41517	20	5.86 m	73 mm	5.850 mm × approx. 500 mm × 75 mm	13.2 kg	1.09 m	6.6 m
41518	24	6.98 m	85 mm	6.980 mm × approx. 500 mm × 85 mm	16 kg	1.2 m	7.7 m

Alto L



Details

The compact alternative - with respect to size, weight and price/performance ratio.

- Rung depth: 30 mm
- Very light but still extremely stable.
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
Standards	EN 131 professional
Material	Aluminium
Coating	natural
Connection Stile-Rung	flanged
Tread depth	30 mm
Load	max. 150 kg
Pitch rung/tread	270 mm
Producttype	Flanged single ladder with rungs
Type rung/tread	serrated

Variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41547	7	2.21 m	58 mm	2.210 mm × 350 mm × 60 mm	4 kg		3.05 m
41548	8	2.49 m	58 mm	2.490 mm × 350 mm × 60 mm	4.4 kg		3.35 m
41550	10	3.05 m	58 mm	3.050 mm × 350 mm × 60 mm	6.1 kg	0.79 m	3.9 m
41552	12	3.61 m	58	3.610 mm × 350 mm ×	7 kg	0.79 m	4.4 m

		mm		60 mm			
41554	14	4.17 m	62 mm	4.170 mm × 350 mm × 65 mm	8 kg	0.79 m	4.95 m
41556	16	4.73 m	68 mm	4.730 mm × 350 mm × 70 mm	9.2 kg	0.89 m	5.5 m
41558	18	5.29 m	73 mm	5.290 mm × 350 mm × 80 mm	10.5 kg	0.89 m	6.05 m
41560	20	5.85 m	73 mm	5.850 mm × 350 mm × 80 mm	11.5 kg	0.99 m	6.6 m
41562	22	6.41 m	73 mm	6.410 mm × 350 mm × 80 mm	13.2 kg	0.99 m	7.15 m
41564	24	6.98 m	85 mm	6.970 mm × 350 mm × 90 mm	14.4 kg	1.1 m	7.7 m

Strato DL



Details

The inexpensive alternative for safe ascent and quick and flexible application.

- Robust extruded-section triangular rungs with step horizontal in working position.
- Outside width: 350 mm.
- Special rung design creates a broad step area.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

- High strength, non-twist rung/stile connections.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty 10 years

Standards EN 131 professional

Material Aluminium

Coating natural

Connection Stile-Rung flanged

Tread depth 38 mm

Load max. 150 kg

Pitch rung/tread 265 mm

Producttype Flanged single ladder with rungs

Type rung/tread serrated

Variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
44808	8	2.42 m	58 mm	2.420 mm × 360 mm × 60 mm	4.3 kg		3.3 m
44810	10	2.98 m	58 mm	2.980 mm × 360 mm × 60 mm	5.3 kg		3.85 m
44812	12	3.54 m	68 mm	3.540 mm × 360 mm × 70 mm	7.9 kg	0.79 m	4.4 m
44814	14	4.11 m	73 mm	4.110 mm × 360 mm × 75 mm	9.2 kg	0.79 m	4.9 m
44816	16	4.67 m	73 mm	4.660 mm × 360 mm × 75 mm	10.1 kg	0.89 m	5.45 m
44818	18	5.23 m	73 mm	5.220 mm × 360 mm × 75 mm	11.2 kg	0.89 m	6 m

44819	20	5.9 m	73 mm	5.780 mm × 360 mm × 75 mm	12.4 kg	0.99 m	6.55 m
-------	----	-------	-------	---------------------------	---------	--------	--------

EFA L



Details

The safety ladder for quick application in chemical or electrical environments.

- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Outside width: 420 mm - particularly stable.

Hints and special features

- in accordance with DIN EN 131-1, order No. 41255 includes a stabiliser bar.
- Complies with EN 131 Professional.

More Information

Warranty	10 years
Standards	EN 131 professional
Material	Glass-fibre reinforced plastic
Coating	natural
Tread depth	30 mm
Load	max. 150 kg
Pitch rung/tread	265 mm
Producttype	GRP single ladder with rungs
Type rung/tread	serrated
Stile depth	58 mm

Variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41251	6	1.92 m	58 mm	1.924 mm × 430 mm × 70 mm	5.6 kg		2.8 m
41253	10	2.993 m	58 mm	3.044 mm × 430 mm × 70 mm	8.6 kg		3.85 m
41255	14	4.16 m	73 mm	4.164 mm × 430 mm × 70 mm	12.4 kg	0.9 m	4.95 m

Crestamax L



Details

The alternative in material and price: pleasant to grip at all temperatures, popular on building sites and with painters.

- Stiles are made of premium coniferous wood, and treads made of beech.
- Tensioning screws for additional safety and stability.
- Low thermal conductivity - always pleasant to grip, even when used outdoors in winter.
- Outside width: 380 mm.
- Glued and coated mortise and tenon joints between rungs and stiles.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty10 years

StandardsEN 131 professional

Material	Wood
Coating	natural
Connection Stile-Rung	adhesive-bonded
Tread depth	21 mm
Load	max. 150 kg
Pitch rung/tread	270 mm
Producttype	Timber single ladder with rungs

Variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Working height
40008	8	2.37 m	66 mm	2.370 mm × 380 mm × 66 mm	6.5 kg	3.35 m
40010	10	2.93 m	66 mm	2.930 mm × 380 mm × 66 mm	8.5 kg	3.9 m

Compactstep L



Details

The world champion when it comes to space-saving: extremely small format for transport, but wide rungs for a secure standing surface.

- When pushed together, the ladder fits into any luggage compartment.
- Can be adjusted to different heights - several ladders in one. As a result, it can be always be at the suitable height.
- Wide rungs for comfortable ascent and descent.
- Abrasion-resistant, anodised stiles.

Hints and special features

- Complies with EN 131-6.

More Information

Warranty	10 years
Standards	EN 131-6
adjustable-height-pf	1
Material	Aluminium
Coating	anodised
Tread depth	40 mm
Load	max. 150 kg
Pitch rung/tread	300 mm
Producttype	Telescopic single ladder with rungs
Type rung/tread	serrated

Variants

Order number	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece	Working height
40400	9	2.66 m	0.76 m	760 mm × 470 mm × 80 mm	8.4 kg		3.4 m
40410	11	3.23 m	0.82 m	approx. 800 mm × approx. 500 mm × approx. 100 mm	13 kg	0.8 m	4 m
40401	13	3.8 m	0.88 m	880 mm × 500 mm × 100 mm	14 kg	0.88 m	4.5 m

Telescopic single ladder



Details

The world champion when it comes to space-saving: extremely small format for transport, but wide rungs for a secure standing surface.

- When pushed together, the ladder fits into any luggage compartment.
- Can be adjusted to different heights - several ladders in one. As a result, it can be always be at the suitable height.
- Treads with a depth of 80 mm for fatigue-free standing.
- Silicone anti-friction buffers in the stiles ensure maximum safety during telescoping.
- New triangular stile for increased stability and resistance to torsion.
- Abrasion-resistant, anodised stiles.
- Original TELESTEPS - the product innovation by the inventor of the telescopic ladder.

Hints and special features

- Complies with EN 131-6.

More Information

Warranty	10 years
Standards	EN 131-6
adjustable-height-pf	0
Material	Aluminium
Coating	anodised
Tread depth	80 mm
Load	max. 150 kg
Pitch rung/tread	300 mm
Type rung/tread	serrated

Variants

Order number	Number of treads	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Working height
40385	9	2.9 m	0.76 m	approx. 810 mm × approx. 470 mm × approx. 110 mm	10.2 kg	approx. 3.8 m
40386	11	3.5 m	0.87 m	approx. 880 mm × approx. 560 mm × approx. 120 mm	15.2 kg	approx. 4.3 m

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru