

Plazamax P

This tried and tested access solution is very compact when folded and has rubber coating for safe and comfortable standing.

Product description

- Large standing area: 230 x 360 mm.
- Large steps for safe and comfortable standing, with rubber surface.
- Collapsible for extra compactness.
- Safety bar with practical storage tray, optional on the 3-step variant, attached as standard on the 4- or 5-step variant.
- Stile ends with plastic edge finish.
- Stiles made from extruded aluminium sections for maximum stability.



Product features

Coating: natural
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 250 mm
Platform length: 230 mm
Platform width: 360 mm
Producttype: Safety steps
Standards: EN 14183
Stile depth: 70 mm
Tray: Plastic
Tread depth: 230 mm
Type rung/tread: with non-slip rubber coating
Warranty: 10 years

Hints and special features

Folds to a compact size for transport and storage.
Complies with EN 14 183

Product variants

Order number	Number of rungs, incl. platform	Overall base width	Platform height	Safety bow	Transport dimensions	Weight	Working height
41927	2	0.48 m	0.45 m	No	560 mm x 500 mm x 90 mm	3.9 kg	2.45 m
41923	3	0.56 m	0.7 m	No	1.140 mm x 560 mm x 80 mm	6.6 kg	2.7 m
41928	3	0.56 m	0.7 m	Yes	1.140 mm x 570 mm x 130 mm	8.4 kg	2.7 m
41926	4	0.57 m	0.9 m	Yes	1.450 mm x 580 mm x 140 mm	10.6 kg	2.9 m
41925	5	0.6 m	1.15 m	Yes	1.760 mm x 580 mm x 140 mm	12.8 kg	3.15 m

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47



Plazatec P

Sturdy step solution with compact dimensions when folded and ribbed sheet metal for safe standing.

Product description

- Large standing area: 230 x 360 mm.
- Large steps for safe and comfortable standing, with ribbed sheet metal surface.
- Collapsible for extra compactness.
- Safety bar with practical storage tray, optional on the 3-step variant, attached as standard on the 4- or 5-step variant.
- Stile ends with plastic edge finish.
- Stiles made from extruded aluminium sections for maximum stability.



Product features

Coating: natural
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 250 mm
Platform length: 230 mm
Platform width: 360 mm
Producttype: Safety steps
Standards: EN 14183
Stile depth: 70 mm
Tray: Plastic
Tread depth: 230 mm
Type rung/tread: serrated
Warranty: 10 years

Hints and special features

Folds to a compact size for transport and storage.
Complies with EN 14 183

Product variants

Order number	Number of rungs, incl. platform	Overall base width	Platform height	Safety bow	Transport dimensions	Weight	Working height
41673	3	0.56 m	0.7 m	No	1.140 mm × 570 mm × 80 mm	6.6 kg	2.7 m
41683	3	0.56 m	0.7 m	Yes	1.150 mm × 580 mm × 130 mm	8.4 kg	2.7 m
41684	4	0.57 m	0.9 m	Yes	1.460 mm × 590 mm × 130 mm	10.6 kg	2.9 m
41685	5	0.6 m	1.15 m	Yes	1.770 mm × 610 mm × 130 mm	12.8 kg	3.15 m



ZARGES

Plazatec P

The quick and flexible solution that can be folded to space-saving size for transport.

Product description

- Minimum space requirement for storage and transport.
- Non-slip serrated aluminium treads.
- Work comfortably and safely on a large standing surface (treads 360 mm wide and 230 mm deep).
- Stiles made from extruded aluminium sections for maximum stability.
- Stile ends with plastic edge finish.

Product features

Coating: natural
Load: max. 150 kg
Material: Aluminium
Overall base width: 0.48 m
Pitch rung/tread: 250 mm
Platform length: 230 mm
Platform width: 360 mm
Producttype: Safety steps
Safety bow: No
Standards: EN 14183
Stile depth: 70 mm
Tread depth: 230 mm
Type rung/tread: serrated
Warranty: 10 years



Hints and special features

Folds to a compact size for transport and storage.
Complies with EN 14 183



Plazastep P

The flexible alternative for safe standing and an optimum price/performance ratio.

Product description

- Collapsible for extra compactness.
- Light-alloy treads 205 x 360 mm for safe and comfortable standing.
- Safety bar with practical storage tray, optional on the 3-step variant, attached as standard on the 4- or 5-step variant.
- Order Nos. 41493 and 41494 with castors as standard, for easy movement of the steps.
- Stile ends with plastic edge finish.

Product features

Coating: natural
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 220 mm
Platform length: 205 mm
Platform width: 360 mm
Producttype: Safety steps
Standards: EN 14183
Stile depth: 68 mm
Tray: Plastic
Tread depth: 205 mm
Type rung/tread: serrated
Warranty: 10 years



Hints and special features

Folds to a compact size for transport and storage.
Complies with EN 14 183

Product variants

Order number	Number of rungs, incl. platform	Overall base width	Platform height	Safety bow	Transport dimensions	Weight	Working height
41490	2	0.55 m	0.44 m	No	770 mm × 530 mm × 70 mm	4.7 kg	2.45 m
41491	3	0.57 m	0.66 m	No	1.080 mm × 550 mm × 70 mm	7 kg	2.65 m
41493	3	0.57 m	0.66 m	Yes	1.070 mm × 550 mm × 110 mm	8.5 kg	2.65 m
41494	4	0.59 m	0.88 m	Yes	1.380 mm × 575 mm × 115 mm	10.5 kg	2.9 m
41495	5	0.6 m	1.1 m	Yes	1.710 mm × 630 mm × 140 mm	13 kg	3.1 m

Workmaster Plus P

Extremely non-slip and comfortable: Folding work platform with R13 platform surface.

Product description

- Extremely non-slip platform surface in accordance with the specifications of quality class R13.
- Increased safety even with oily substances or ice during outdoor applications.
- Also available with wooden surface as standard version.
- Platform dimensions 1.70 x 0.60 m.
- Total permissible load for the platform is 300 kg - which means it can be used by two persons.
- Folds to extremely small dimensions for transport and storage.
- Comfortable access via 60 mm-deep aluminium alloy rungs.



Product features

Base: 2,21 m × 0,74 m
 Coating: natural
 Connection Stile-Rung: flanged
 Dimensions, folded: 1,77 m × 0,74 m × 0,17 m
 Length: 1.77 m
 Load: max. 300 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Platform height: 0.7 m
 Platform length: 1700 mm
 Platform width: 600 mm
 Producttype: Work platform
 Transport dimensions: 1.771 mm × 741 mm × 150 mm
 Tread depth: 60 mm
 Type rung/tread: serrated
 Warranty: 10 years
 Width: 0.74 m
 Working height: 2.7 m

AMA P

The modular solution for flexible or stationary application: extendible from a step stool to a complete work platform in various heights.

Product description

- Modular design for changing or expanding configurations at any time – as mobile or stationary walkways.
- Lightweight for quick and easy handling.
- Extremely robust, torsion-resistant, corrosion-proof aluminium alloy structure.
- Comfortable, safe steps (555 x 250 mm) made from serrated aluminium sheet.
- Two-step basic module with up to three add-on steps, suitable for mobile applications.
- Wide range of accessories for stationary or mobile applications.
- Add-on modules in four different heights.



Hints and special features

Complies with EN 14 183

Product features

Coating: natural
 Connection Stile-Rung: welded
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 200 mm
 Platform length: 250 mm
 Platform width: 555 mm
 Producttype: Modular work platform
 Standards: EN 14183
 Tread depth: 250 mm
 Type rung/tread: serrated
 Warranty: 10 years

Product variants

Order number	Module combination	Module, individual	Overall platform depth	Platform height	Total max. weight	Transport dimensions	Weight
40261	A	Module A	0.3 m	0.2 m	2.9 kg	580 mm × 290 mm × 200 mm	2.9 kg
40260	B	Module B	0.55 m	0.4 m	4.8 kg	620 mm × 550 mm × 400 mm	4.8 kg
40262	B + C	Module C	0.8 m	0.4 m	8.7 kg	610 mm × 280 mm × 380 mm	3.9 kg
40263	B + D	Module D	0.8 m	0.6 m	9.2 kg	630 mm × 290 mm × 590 mm	4.4 kg
40264	B + D + E	Module E	1.05 m	0.8 m	14 kg	660 mm × 290 mm × 790 mm	4.8 kg
40265	B + D + E + F	Module F	1.3 m	0.99 m	19.5 kg	690 mm × 290 mm × 980 mm	5.5 kg

AFA P

The basic step stool with low weight, high stability and a comfortable standing area.

Product description

- 200 mm deep steps made of non-slip ribbed aluminium plate.
- 350 x 577 mm standing platform braced by a cross-strut.
- High-strength, welded tubular aluminium construction ensures stability and long service life.
- Maximum stability thanks to a wide standing surface.
- Stile ends with plastic edge finish.



Product features

Coating: natural
 Connection Stile-Rung: welded
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 200 mm
 Platform length: 350 mm
 Platform width: 577 mm
 Producttype: Step stool
 Standards: EN 14183
 Tread depth: 200 mm
 Type rung/tread: serrated
 Warranty: 10 years

Hints and special features

Self-locking sprung castors available as an accessory from two steps upwards. Handrail available as an accessory from three steps upwards.
 Complies with EN 14 183

Product variants

Order number	Base	Number of rungs, incl. platform	Platform height	Transport dimensions	Weight	Working height
40031	0,4 m × 0,6 m	1	0.2 m	600 mm × 406 mm × 200 mm	3 kg	2.2 m
40032	0,64 m × 0,67 m	2	0.4 m	671 mm × 639 mm × 400 mm	5.5 kg	2.4 m
40033	0,87 m × 0,69 m	3	0.6 m	692 mm × 871 mm × 600 mm	7.8 kg	2.6 m
40034	1,1 m × 0,71 m	4	0.8 m	713 mm × 1.103 mm × 800 mm	10.1 kg	2.8 m
40035	1,35 m × 0,73 m	5	0.99 m	734 mm × 1.336 mm × 1.000 mm	13.5 kg	3 m

Seventec RC SP

Can be folded for space-saving transport and storage, perfect for outdoor applications thanks to profiled treads.

Product description

- 85 mm deep treads with perforation to allow liquids to flow off and profiling to ensure stability.
- Platform size approx. 600 x 300 mm.
- Reflective strips on the stiles to improve visibility in poor visual conditions.
- Rigid connection on both sides.
- Practical tray with plenty of space for tools and small items.
- Extra-wide treads and comfortable surfaces to stand on.
- Single-sided access.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Safety bar for comfortable and safe working.



Product features

Coating: natural
 Connection Stile-Rung: riveted
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 218 mm
 Platform length: 300 mm
 Platform width: 600 mm
 Producttype: Riveted work platform
 Tray: Aluminium
 Tread depth: 85 mm
 Type rung/tread: RC tread
 Warranty: 10 years

Hints and special features

Complies with EN 14 183

Product variants


Order number	Number of rungs, incl. platform	Overall base width	Platform height	Standards	Transport dimensions	Weight	Working height
40233	3	0.67 m	0.66 m	EN 14183	1.450 mm × 598 mm × 660 mm	8.1 kg	2.66 m
40234	4	0.69 m	0.86 m	EN 14183	1.680 mm × 623 mm × 860 mm	10.3 kg	2.86 m
40235	5	0.72 m	1.08 m	EN 131 professional	1.700 mm × 700 mm × 300 mm	11.7 kg	3.08 m

Seventec RC BP

Lightweight and comfortable platform with profiled treads and platform for outdoor applications for quick and flexible use.

Product description

- 85 mm deep treads with perforation to allow liquids to flow off and profiling to ensure stability.
- Platform size approx. 600 x 300 mm.
- Reflective strips on the stiles to improve visibility in poor visual conditions.
- Rigid connection on both sides.
- Extra-wide treads and comfortable surfaces to stand on.
- Double-sided access.
- Platform with integrated hinged connection for maximum stability and rigidity.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.



Product features

Coating: natural
 Connection Stile-Rung: riveted
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 218 mm
 Platform length: 300 mm
 Platform width: 600 mm
 Producttype: Riveted work platform
 Standards: EN 14183
 Tread depth: 85 mm
 Type rung/tread: RC tread
 Warranty: 10 years

Hints and special features

Comfortable and safe standing through 600 × 300 mm work platform.
 Complies with EN 14 183

Product variants

Order number	Number of treads	Number of treads	Overall base width	Platform height	Transport dimensions	Weight	Working height
40392	2	2 × 2	0.7 m	0.49 m	610 mm × 700 mm × 290 mm	5.2 kg	2.49 m
40393	3	2 × 3	0.75 m	0.74 m	860 mm × 750 mm × 290 mm	7.3 kg	2.74 m
40394	4	2 × 4	0.8 m	0.99 m	1.110 mm × 800 mm × 290 mm	10.2 kg	2.99 m

Seventec BP

Lightweight and comfortable platform with large standing area for quick and flexible application.


Product description

- Platform size approx. 600 x 300 mm.
- Treads 85 mm deep for safe standing.
- Rigid connection on both sides.
- Extra-wide treads and comfortable surfaces to stand on.
- Double-sided access.
- Platform with integrated hinged connection for maximum stability and rigidity.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.



Product features

Coating: natural
 Connection Stile-Rung: riveted
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 218 mm
 Platform length: 300 mm
 Platform width: 600 mm
 Producttype: Riveted work platform
 Standards: EN 14183
 Tread depth: 85 mm
 Type rung/tread: serrated
 Warranty: 10 years



Hints and special features

Comfortable and safe standing through 600 x 300 mm work platform.
 Complies with EN 14 183

Product variants

Order number	Number of treads	Number of treads	Overall base width	Platform height	Transport dimensions	Weight	Working height
40372	2	2 x 2	0.7 m	0.49 m	610 mm x 700 mm x 290 mm	5.7 kg	2.49 m
40373	3	2 x 3	0.75 m	0.74 m	860 mm x 750 mm x 290 mm	7.9 kg	2.74 m
40374	4	2 x 4	0.8 m	0.99 m	1.110 mm x 800 mm x 290 mm	10.3 kg	2.99 m



Bigfoot P

This versatile and flexible all-round talent is extremely stable thanks to its patented automatic locking mechanism.

Product description

- Serrated, non-slip standing surface.
- Mobile version with self-locking sprung castors.
- Extremely stable thanks to patented automatic locking mechanism and non-slip rubber lip.
- Platform diameter of 30 cm for safe standing.

Product features

Diameter, bottom: 0.44 m
Diameter, centre: 0.36 m
Diameter, top: 0.29 m
Load: max. 150 kg
Material: Polypropylene
Pitch rung/tread: 215 mm
Platform height: 0.43 m
Producttype: Mobile step stool
Standards: EN 14183
Transport dimensions: 400 mm × 230 mm × 400 mm
Type rung/tread: serrated
Warranty: 10 years
Weight: 2.6 kg
Working height: 2.45 m



Hints and special features

Safe standing thanks to patented locking mechanism.
Complies with EN 14 183



ZARGES

Workstand P

Optimal stability combined with a large standing surface and easy handling.

Product description

- Platform size approx. 400 x 300 mm.
- Rugged steel frame for great stability.
- Easy-to-handle thanks to the handle in the platform.

Product features

Base: 0,62 m × 0,52 m

Coating: powder-coated

Load: max. 150 kg

Material: Plastic / steel

Platform height: 0.4 m

Platform length: 400 mm

Platform width: 300 mm

Producttype: Work platform

Transport dimensions: 620 mm × 520 mm × 410 mm

Warranty: 10 years

Weight: 5 kg

Working height: 2.4 m



Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Пермь (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru