

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru

Push-up ladders



Everest 2E

Details

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty

10 years

Standards

EN 131 professional

Material	Aluminium
Coating	natural
Connection Stile-Rung	flanged
Tread depth	30 mm
Load	max. 150 kg
Wheels	Rubber
Number ladderparts	2
Pitch rung/tread	270 mm
Producttype	Flanged push-up ladder with rungs, 2-section
Type rung/tread	serrated
External width of lower ladder	490 mm

Variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overa ll lengt h, retrac ted	Stil e de pth	Transport dimensions	Weight	Wide crossp iece	Wor kin g hei ght
40245	6	2 × 6	2.95 m	1.83 m	58 mm	1.830 mm × 500 mm × 130 mm	6 kg		3.8 m
40246	8	2 × 8	4.07 m	2.39 m	68 mm	2.390 mm × 500 mm × 130 mm	9.8 kg	0.9 m	4.85 m
40247	10	2 × 10	4.96 m	3 m	68 mm	3.000 mm × 500 mm × 140 mm	13.5 kg	1 m	5.75 m
40248	12	2 × 12	6.09 m	3.56 m	73 mm	3.570 mm × 500 mm × 160 mm	18 kg	1.1 m	6.8 m
40249	14	2 × 14	7.21 m	4.07 m	73 mm	4.130 mm × 500 mm × 160 mm	19.5 kg	1.2 m	7.9 m

40214	16	2 × 16	8.33 m	4.7 m	98 mm	4.690 mm × 500 mm × 180 mm	25 kg	1.2 m	9 m
40215	18	2 × 18	9.13 m	5.2 m	98 mm	5.210 mm × 500 mm × 230 mm	27.5 kg	1.2 m	9.75 m
40216	20	2 × 20	10.25 m	5.74 m	114 mm	5.770 mm × 500 mm × 230 mm	33 kg	1.2 m	10.85 m
40217	24	2 × 24	12.22 m	6.9 m	114 mm	6.900 mm × 500 mm × 230 mm	41.54 kg	1.2 m	12.75 m

Everest Plus 2E

Details

Better footing at the top. The push-up ladder with 80 mm deep treads instead of rungs.

- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- Upper ladder fitted with plastic wall wheels.
- Height adjustment in increments of 280 mm.
- Locks safely by means of hooks with lift-off retainer.
- Ladder width: 420 mm.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.



More Information

Warranty 10 years

Standards EN 131 professional

adjustable-height-pf 1

Material Aluminium

Coating natural

Connection Stile-Rung	flanged
Load	max. 150 kg
Wheels	Rubber
Pitch rung/tread	265 mm
Producttype	Flanged push-up ladder with treads, two-section
External width of lower ladder	420 mm
Stile depth	73 mm

Variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide cross piece	Working height
40467	8	2 × 8	4.2 m	2.52 m	approx. 2.520 mm × approx. 420 mm × approx. 200 mm	11.5 kg	0.9 m	4.9 m
40468	10	2 × 10	5.32 m	3.08 m	approx. 3.080 mm × approx. 420 mm × approx. 200 mm	13.9 kg	1 m	5.95 m
40469	12	2 × 12	6.44 m	3.64 m	approx. 3.640 mm × approx. 420 mm × approx. 200 mm	17 kg	1.1 m	7 m

Everest 2DE

Details

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- External width of lower ladder: 420 mm.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
Standards	EN 131 professional
Material	Aluminium
Coating	natural
Connection Stile-Rung	flanged
Tread depth	38 mm
Load	max. 150 kg
Number ladderparts	2
Pitch rung/tread	265 mm
Producttype	Flanged push-up ladder with rungs, 2-section
Type rung/tread	serrated
External width of lower ladder	420 mm

Variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide cross piece	Working height
44834	8	2 × 8	3.8 m	2.42 m	58 mm	2.420 mm × 420 mm × 115 mm	9.3 kg	0.8 m	4.6 m
44820	10	2 × 10	4.93 m	2.98 m	68 mm	2.980 mm × 430 mm × 120 mm	11.3 kg	0.9 m	5.65 m
44822	12	2 × 12	6.05 m	3.54 m	68 mm	3.540 mm × 430 mm × 135 mm	15.4 kg	1 m	6.8 m
44824	14	2 × 14	7.17 m	4.1 m	85 mm	4.100 mm × 430 mm × 135	17.8 kg	1.1 m	7.85 m

mm									
44826	16	2 × 16	8.29 m	4.66 m	85 mm	4.660 mm × 430 mm × 145 mm	21.5 kg	1.2 m	8.7 m
44828	18	2 × 18	9.17 m	5.23 m	85 mm	5.230 mm × 430 mm × 145 mm	23.9 kg	1.2 m	9.8 m

Everest EFA 2E

Details

Plastic ladder for access to great heights, for use in electrical and chemical environments.

- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 41288-41290.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
Standards	EN 131 professional
Material	Glass-fibre reinforced plastic
Tread depth	30 mm
Load	max. 150 kg
Number ladderparts	2
Pitch rung/tread	270 mm
Producttype	GRP push-up ladder with rungs, 2-section
Type rung/tread	serrated

External width of lower ladder 420 mm

Variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece	Working height
41288	8	2 × 8	4.17 m	2.44 m	2.500 mm × 430 mm × 125 mm	14.3 kg	0.8 m	4.95 m
41290	10	2 × 10	4.91 m	2.95 m	2.950 mm × 430 mm × 150 mm	19.5 kg	0.9 m	5.7 m
41292	12	2 × 12	6.03 m	3.51 m	3.510 mm × 430 mm × 150 mm	23.3 kg	1 m	6.75 m

Everest 3DE

Details

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Overall width of bottom section: 490 mm.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty10 years

StandardsEN 131 professional

MaterialAluminium

Coatingnatural

Connection Stile-Rung	flanged
Tread depth	38 mm
Load	max. 150 kg
Number ladderparts	3
Pitch rung/tread	265 mm
Producttype	Flanged push-up ladder with rungs, 3-section
Type rung/tread	serrated
External width of lower ladder	490 mm

Variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Width cross piece	Working height
44851	8	3 × 8	5.25 m	2.41 m	68 mm	2.410 mm × 500 mm × 170 mm	15.3 kg	0.9 m	5.95 m
44852	10	3 × 10	6.65 m	2.97 m	73 mm	2.970 mm × 500 mm × 190 mm	19.2 kg	1.1 m	7.25 m
44853	12	3 × 12	8.33 m	3.53 m	85 mm	3.530 mm × 500 mm × 190 mm	24.2 kg	1.2 m	8.8 m
44854	14	3 × 14	9.45 m	4.09 m	85 mm	4.090 mm × 500 mm × 190 mm	36 kg	1.2 m	9.9 m

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новобрянск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru