

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru

Rope-operated ladders



Skyline 2E

Details

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty 10 years

Standards EN 131 professional

Material Aluminium

Coating	natural
Connection Stile-Rung	flanged
Tread depth	30 mm
Load	max. 150 kg
Wheels	Rubber
Number ladderparts	2
Pitch rung/tread	270 mm
Producttype	Flanged rope-operated ladder with rungs, 2-section
Type rung/tread	serrated
External width of lower ladder	490 mm

Variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Stile depth	Transport dimensions	Weight	Working height
40206	14	2 × 14	7.21 m	4.14 m	73 mm	73mm	approx. 4.150 mm × approx. 520 mm × approx. 160 mm	22.821 kg	7.9 m
40207	16	2 × 16	8.33 m	4.7 m	98 mm	98mm	approx. 4.670 mm × approx. 520 mm × approx. 200 mm	24.723 kg	9 m
40208	18	2 × 18	9.13 m	5.2 m	98 mm	98mm	approx. 5.200 mm × approx. 520 mm × approx. 200 mm	30.929 kg	9.75 m
40209	20	2 × 20	10.25 m	5.74 m	114 mm	114mm	approx. 5.740 mm × approx. 520 mm × approx. 220 mm	33.832 kg	10.85 m

40212	22	2 × 22	11.1 m	6.4 m	114 mm	114mm	approx. 6.410 mm × approx. 520 mm × approx. 220 mm	37.936 kg	11.7 m
40210	24	2 × 24	12.22 m	6.9 m	114 mm	114mm	approx. 6.910 mm × approx. 520 mm × approx. 220 mm	42.641 kg	12.75 m

Skyline 3E

Details

When you need access to great heights: Optimised transport dimensions, working heights of up to 16.35 m with convenient height adjustment.

- Two ropes so that centre and top sections can be adjusted separately.
- Rung-by-rung height adjustment in a grid of 280 mm.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- Locks securely thanks to automatic spring loaded pawls.
- The ladders with the Order Nos. 40448 and 40449 are equipped with 2 light alloy supports for easy erection and stabilisation. (Not to be used as free-standing ladders!)
- Improved plastic guide.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty 10 years

Standards EN 131 professional

Material Aluminium

Coating natural

Connection Stile-Rung flanged

Tread depth 30 mm

Load max. 150 kg

Wheels Rubber

Number ladderparts 3

Pitch rung/tread	270 mm
Producttype	Flanged rope-operated ladder with rungs, 3-section
Type rung/tread	serrated
Stile depth	98 mm

Variants

Order number	External width of lower ladder	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Stile depth	Transport dimensions	Weight	Working height
40446	560 mm	15	3 × 15	10.55 m	4.4 m	86 mm	86mm / 98mm	4.420 mm × 565 mm × 228 mm	45 kg	11.15 m
40447	560 mm	18	3 × 18	12.55 m	5.25 m	86 mm	86mm / 98mm	5.260 mm × 565 mm × 228 mm	53 kg	13.1 m
40448	590 mm	20	3 × 20	14.2 m	5.8 m	98 mm	98mm / 98mm	5.820 mm × 718 mm × 242 mm	68 kg	14.7 m
40449	590 mm	22	3 × 22	15.9 m	6.4 m	98 mm	98mm / 98mm	6.420 mm × 718 mm × 242 mm	74 kg	16.35 m

Skyline EFA 2E

Details

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
----------	----------

Standards	EN 131 professional
-----------	---------------------

Material	Glass-fibre reinforced plastic
----------	--------------------------------

Tread depth	30 mm
-------------	-------

Load	max. 150 kg
------	-------------

Wheels	Rubber
--------	--------

Number ladderparts	2
--------------------	---

Pitch rung/tread	270 mm
------------------	--------

Producttype	GRP rope-operated ladder with rungs, 2-section
-------------	--

Type rung/tread	serrated
-----------------	----------

External width of lower ladder	420 mm
--------------------------------	--------

Stile depth	90 mm
-------------	-------

Variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide cross piece	Working height
41274	14	2 × 14	7.17 m	4.09 m	4.100 mm × 470 mm × 150 mm	35.7 kg	1.1 m	7.95 m
41276	16	2 × 16	7.72 m	4.64 m	4.650 mm × 450	41.3	1.2 m	8.5 m

А лматы (7273)495-231	И ваново (4932)77-34-06	М агнитогорск (3519)55-03-13	Р остов-на-Дону (863)308-18-15	Т ольятти (8482)63-91-07
А нгарск (3955)60-70-56	И жевск (3412)26-03-58	М осква (495)268-04-70	Р язань (4912)46-61-64	Т омск (3822)98-41-53
А рхангельск (8182)63-90-72	И ркутск (395)279-98-46	М урманск (8152)59-64-93	С амара (846)206-03-16	Т ула (4872)33-79-87
А страхань (8512)99-46-04	К азань (843)206-01-48	Н абережные Челны (8552)20-53-41	С анкт-Петербург (812)309-46-40	Т юмень (3452)66-21-18
Б арнаул (3852)73-04-60	К алининград (4012)72-03-81	Н ижний Новгород (831)429-08-12	С аратов (845)249-38-78	У льяновск (8422)24-23-59
Б елгород (4722)40-23-64	К алуга (4842)92-23-67	Н овокузнецк (3843)20-46-81	С евастополь (8692)22-31-93	У лан-Удэ (3012)59-97-51
Б лаговещенск (4162)22-76-07	К емерово (3842)65-04-62	Н оябрьск (3496)41-32-12	С аранск (8342)22-96-24	У фа (347)229-48-12
Б рянск (4832)59-03-52	К иров (8332)68-02-04	Н овосибирск (383)227-86-73	С имферополь (3652)67-13-56	Х абаровск (4212)92-98-04
В ладивосток (423)249-28-31	К оломна (4966)23-41-49	О мск (3812)21-46-40	С моленск (4812)29-41-54	Ч ебоксары (8352)28-53-07
В ладикавказ (8672)28-90-48	К острома (4942)77-07-48	О рел (4862)44-53-42	С очи (862)225-72-31	Ч елябинск (351)202-03-61
В ладимир (4922)49-43-18	К раснодар (861)203-40-90	О ренбург (3532)37-68-04	С таврополь (8652)20-65-13	Ч ереповец (8202)49-02-64
В олгоград (844)278-03-48	К расноярск (391)204-63-61	П енза (8412)22-31-16	С ургут (3462)77-98-35	Ч ита (3022)38-34-83
В ологда (8172)26-41-59	К урск (4712)77-13-04	П етрозаводск (8142)55-98-37	С ыктывкар (8212)25-95-17	Я кутск (4112)23-90-97
В оронеж (473)204-51-73	К урган (3522)50-90-47	П сков (8112)59-10-37	Т амбов (4752)50-40-97	Я рославль (4852)69-52-93
Е катеринбург (343)384-55-89	Л ипецк (4742)52-20-81	П ермь (342)205-81-47	Т верь (4822)63-31-35	
Россия +7(495)268-04-70		Казахстан +7(7172)727-132	Киргизия +996(312)96-26-47	

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru