

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru

Stepladders, single-sided access



Megastep S

Details

The strongest of all our ladders: high load capacity and modern design for the most exacting requirements.

- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Black, wear-resistant anodised stiles.
- Large standing platform (250 x 250 mm) made from extruded aluminium sections for safe and comfortable standing even when working for long periods.
- Practical aluminium storage tray for small items and tools.
- High-strength Perlon belts prevent splay, on models with 5 rungs or more.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty 10 years

Standards EN 131 professional

Platform width 250 mm

Material	Aluminium
Platform length	250 mm
Anti splay	Belt strap
Coating	anodised
Connection Stile-Rung	flanged
Tread depth	60 mm
Load	max. 250 kg
Tray	Aluminium
Pitch rung/tread	265 mm
Producttype	Flanged stepladder with rungs
Type rung/tread	SL Step
Stile depth	73 mm
Stile depth	58 mm

Variants

Order number	Anti splay	Base	No. of rungs incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weight	Working height
41145		0,76 m × 0,44 m	3	0.44 m	1.59 m	0.8 m	1.595 mm × 445 mm × 150 mm	6.2 kg	2.8 m
41146		0,93 m × 0,47 m	4	0.47 m	1.87 m	1.06 m	1.875 mm × 475 mm × 150 mm	7.3 kg	3.1 m
41147	Belt strap	1,1 m × 0,5 m	5	0.5 m	2.15 m	1.33 m	2.155 mm × 505 mm × 150 mm	8 kg	3.35 m
41148	Belt strap	1,27 m × 0,53 m	6	0.53 m	2.43 m	1.59 m	2.435 mm × 535 mm × 150 mm	8.6 kg	3.6 m
41149	Belt strap	1,61 m × 0,59 m	8	0.59 m	2.99 m	2.12 m	2.995 mm × 595 mm × 150 mm	9.6 kg	4.15 m

R13step S

Details

Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.

- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Practical aluminium storage tray for small items and tools.
- Platform made from extruded aluminium (300 mm × 250 mm) with R13 surface for safer and comfortable standing even when working for longer periods of time.
- High-strength Perlon belts prevent splay, fitted on all models of 5 rungs or more.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
----------	----------

Standards	EN 131 professional
-----------	---------------------

Platform width	300 mm
----------------	--------

Material	Aluminium
----------	-----------

Platform length	250 mm
-----------------	--------

Anti splay	Belt strap
------------	------------

Coating	anodised
---------	----------

Connection Stile-Rung	flanged
-----------------------	---------

Tread depth	80 mm
-------------	-------

Load	max. 150 kg
------	-------------

Tray	Aluminium
------	-----------

Pitch rung/tread	265 mm
------------------	--------

Producttype	Stepladder with flanged treads
-------------	--------------------------------

Type rung/tread	R13 tread
-----------------	-----------

Stile depth	73 mm
-------------	-------

Stile depth	58 mm
-------------	-------

Variants

Order number	Anti splay	Base	Number of rungs, incl.	Overall base	Overall length	Platform height	Transport dimensions	Weight	Working height
--------------	------------	------	------------------------	--------------	----------------	-----------------	----------------------	--------	----------------

platform width									
41636		0,57 m × 0,5 m	3	0.5 m	1.59 m	0.8 m	approx. 1.590 mm × approx. 500 mm × approx. 170 mm	8.3 kg	2.8 m
41637		0,76 m × 0,53 m	4	0.53 m	1.87 m	1.06 m	approx. 1.870 mm × approx. 530 mm × approx. 170 mm	9.8 kg	3.1 m
41638	Belt strap	0,96 m × 0,56 m	5	0.56 m	2.15 m	1.33 m	approx. 2.150 mm × approx. 560 mm × approx. 170 mm	10.5 kg	3.35 m
41639	Belt strap	1,15 m × 0,59 m	6	0.59 m	2.43 m	1.59 m	approx. 2.430 mm × approx. 590 mm × approx. 170 mm	11.5 kg	3.6 m
41640	Belt strap	1,34 m × 0,62 m	7	0.62 m	2.71 m	1.85 m	approx. 2.710 mm × approx. 620 mm × approx. 170 mm	12.3 kg	3.85 m
41641	Belt strap	1,53 m × 0,65 m	8	0.65 m	2.99 m	2.12 m	approx. 2.990 mm × approx. 650 mm × approx. 170 mm	12.8 kg	4.15 m
41642	Belt strap	1,91 m × 0,71	10	0.71 m	3.55 m	2.64 m	approx. 3.550 mm × approx. 710 mm × approx. 170	16.1 kg	4.65 m

Saferstep S

Details

Comfortable and safe ascent with high non-slip performance thanks to Safer Step Technology and robust, stable construction.

- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Practical aluminium storage tray for small items and tools.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- High-strength Perlon belts prevent splay, fitted on all models of 5 rungs or more.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.

Hints and special features

- Complies with EN 131 Professional.



More Information

Warranty	10 years
Standards	EN 131 professional
Platform width	300 mm
Material	Aluminium
Platform length	250 mm
Anti splay	Belt strap
Coating	anodised
Connection Stile-Rung	flanged
Tread depth	80 mm
Load	max. 150 kg
Tray	Aluminium
Pitch rung/tread	265 mm
Producttype	Stepladder with flanged treads
Type rung/tread	Safer Step
Stile depth	68 mm
Stile depth	48 mm

Variants

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weight	Working height
41373		0,75 m × 0,49 m	3	0.49 m	1.59 m	0.8 m	approx. 1.600 mm × approx. 500 mm × 230 mm	6.5 kg	2.8 m
41374		0,91 m × 0,52 m	4	0.52 m	1.87 m	1.06 m	approx. 1.880 mm × approx. 520 mm × approx. 230 mm	7.6 kg	3.1 m
41375	Belt strap	1,08 m × 0,55 m	5	0.55 m	2.15 m	1.33 m	approx. 2.160 mm × approx. 550 mm × approx. 230 mm	9 kg	3.35 m
41376	Belt strap	1,25 m × 0,58 m	6	0.58 m	2.43 m	1.59 m	approx. 2.430 mm × approx. 580 mm × 230 mm	9.9 kg	3.6 m
41377	Belt strap	1,42 m × 0,61 m	7	0.61 m	2.71 m	1.85 m	approx. 2.710 mm × approx. 610 mm × 230 mm	11.1 kg	3.85 m
41378	Belt strap	1,58 m × 0,64 m	8	0.64 m	2.99 m	2.12 m	approx. 2.990 mm × approx. 640 mm × 230 mm	12.3 kg	4.15 m

41380	Belt strap	1,91 m × 0,7 m	10	0.7 m	3.55 m	2.64 m	approx. 3.550 mm × approx. 700 mm × 230 mm	15.6 kg	4.65 m
-------	------------	----------------	----	-------	--------	--------	--	---------	--------

Meistertritt S

Details

Safe standing on very large platform, non-slip ascent and descent thanks to Safer Step Technology. So-called “lightweight platform ladder”.

- 80 mm deep steps with ZARGES Safer Step Technology for fatigue-free standing.
- Particularly large-surface work platform with ribbed aluminium sheet lining (approx. 380 x 390 mm).
- Practical aluminium storage tray for small items and tools.
- With two handrails as standard for safe access.
- Optimum stability thanks to two high-strength Perlon belts for preventing splay.
- Height of the retaining bracket 1,000 mm.
- Treads and stiles made from extruded aluminium sections.

Hints and special features

- Mobile version from 5 steps possible.
- Complies with EN 131 Professional.



More Information

Warranty	10 years
Standards	EN 131 professional
Platform width	390 mm
Material	Aluminium
Platform length	380 mm
Anti splay	Belt strap
Coating	natural
Connection Stile-Rung	flanged
Tread depth	80 mm
Load	max. 150 kg
Tray	Aluminium
Pitch rung/tread	265 mm
Producttype	Stepladder with flanged treads

Type rung/tread

Safer Step

Stile depth

73 mm

Stile depth

58 mm

Variants

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Vertical ladder height	Weight	Working height
41632		0,91 m × 0,59 m	3	0.59 m	1.92 m	0.77 m	1.920 mm × 590 mm × 155 mm	1.77 m	9.5 kg	2.8 m
41633		1,08 m × 0,62 m	4	0.62 m	2.2 m	1.03 m	2.200 mm × 620 mm × 155 mm	2.03 m	10.7 kg	3 m
41634	Belt strap	1,26 m × 0,65 m	5	0.65 m	2.48 m	1.29 m	2.480 mm × 650 mm × 155 mm	2.29 m	12.1 kg	3.3 m
40477	Belt strap	1,43 m × 0,68 m	6	0.68 m	2.75 m	1.55 m	2.750 mm × 680 mm × 155 mm	2.55 m	13.8 kg	3.55 m
40478	Belt strap	1,76 m × 0,74 m	8	0.74 m	3.32 m	2.07 m	3.320 mm × 740 mm × 155 mm	3.07 m	16.7 kg	4.1 m
40479	Belt strap	2,11 m × 0,8 m	10	0.8 m	3.88 m	2.59 m	3.388 mm × 800 mm × 155	3.59 m	20.3 kg	4.6 m

							mm			
41635	Belt strap	2,46 m × 0,86 m	12	0.86 m	4.44 m	3.11 m	4.440 mm × 860 mm × 155 mm	4.11 m	23.3 kg	5.1 m

Comfortstep S

Details

Protection for your shins: high degree of comfort while working through padded treads.

- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Practical aluminium storage tray for small items and tools.
- High-strength Perlon belts prevent splay, fitted on all models of 4 rungs or more.
- Treads with plastic-cushioned front edges.
- Screwed connection between treads and stile.
- Treads and stiles made from extruded aluminium sections.

Hints and special features

- Complies with EN 131 Professional.

More Information	
Warranty	10 years
Standards	EN 131 professional
Platform width	300 mm
Material	Aluminium
Platform length	250 mm
Anti splay	Belt strap
Coating	anodised
Connection Stile-Rung	bolted
Tread depth	80 mm
Load	max. 150 kg
Tray	Aluminium
Pitch rung/tread	250 mm
Producttype	Bolted stepladder with treads
Type rung/tread	padding on front tread edges
Stile depth	42 mm

Variants

Order number	Ant display	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Stile depth	Stile depth steps /back stay	Transport dimensions	Vertical ladder height	Weight	Working height
41421		0,75 m × 0,5 m	3	0.5 m	1.52 m	0.75 m	42 mm	42mm / 42mm	1.520 mm × 500 mm × 150 mm	1.38 m	6.4 kg	2.75 m
41422	Belt strap	0,92 m × 0,53 m	4	0.53 m	1.79 m	1 m	42 mm	42mm / 42mm	1.790 mm × 530 mm × 150 mm	1.63 m	7.4 kg	3 m
41423	Belt strap	1,09 m × 0,56 m	5	0.56 m	2.06 m	1.25 m	42 mm	42mm / 42mm	2.060 mm × 560 mm × 150 mm	1.88 m	8.4 kg	3.25 m
41424	Belt strap	1,27 m × 0,59 m	6	0.59 m	2.33 m	1.5 m	48 mm	48mm / 42mm	2.330 mm × 590 mm × 150 mm	2.13 m	9.7 kg	3.5 m
41425	Belt strap	1,44 m × 0,61 m	7	0.61 m	2.6 m	1.75 m	48 mm	48mm / 42mm	2.600 mm × 615 mm × 150 mm	2.38 m	10.7 kg	3.75 m
41426	Belt strap	1,61 m × 0,64 m	8	0.64 m	2.87 m	2 m	48 mm	48mm / 42mm	2.870 mm × 640 mm × 150 mm	2.63 m	11.9 kg	4 m

41427	Belt strap	1,95 m × 0,7 m	10	0.7 m	3.4 m	2.5 m	48 mm	48mm / 42mm	3.410 mm × 700 mm × 150 mm	3.13 m	14.4 kg	4.5 m
-------	------------	----------------	----	-------	-------	-------	-------	-------------	----------------------------	--------	---------	-------

XLstep S

Details

Low weight, simple handling and a good price/performance ratio with high-value equipment.

- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength Perlon belts prevent splay, fitted on all models of 4 rungs or more.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty	10 years
Standards	EN 131 professional
Platform width	300 mm
Material	Aluminium
Platform length	250 mm
Anti splay	Belt strap
Coating	anodised
Connection Stile-Rung	riveted
Tread depth	80 mm
Load	max. 150 kg
Tray	Aluminium
Pitch rung/tread	250 mm
Producttype	Riveted stepladder with treads
Type rung/tread	serrated
Stile depth	42 mm

Variants

Order number	Anti splay	Base	Num ber of rung s, incl. platf orm	Over all base widt h	Ove rall len gth	Plat for m hei ght	Stil e dep th	Stile dept h step s/ba ck stay	Transpo rt dimensi ons	Vert ical lad der hei ght	W ei gh t	Worki ng height
41223		0,74 m × 0,49 m	3	0.49 m	1.56 m	0.74 m	42 mm	42m m / 42m m	approx. 1.560 mm × approx. 490 mm × approx. 155 mm	1.42 m	6 kg	2.75 m
41224	Belt strap	0,91 m × 0,52 m	4	0.52 m	1.83 m	0.99 m	42 mm	42m m / 42m m	approx. 1.830 mm × approx. 520 mm × approx. 155 mm	1.67 m	6.9 kg	3 m
41225	Belt strap	1,08 m × 0,55 m	5	0.55 m	2.1 m	1.24 m	42 mm	42m m / 42m m	approx. 2.100 mm × approx. 550 mm × approx. 155 mm	1.92 m	7.7 kg	3.25 m
41226	Belt strap	1,25 m × 0,57 m	6	0.57 m	2.37 m	1.49 m	48 mm	48m m / 42m m	approx. 2.370 mm × approx. 570 mm × approx. 155 mm	2.17 m	9.1 kg	3.5 m
41227	Belt strap	1,42 m × 0,61 m	7	0.61 m	2.64 m	1.74 m	48 mm	48m m / 42m m	approx. 2.640 mm × approx. 610 mm × approx. 155 mm	2.42 m	10.2 kg	3.75 m
41228	Belt strap	1,59 m × 0,63 m	8	0.63 m	2.91 m	1.99 m	48 mm	48m m / 42m m	approx. 2.910 mm × approx. 630 mm × approx. 155 mm	2.67 m	11.7 kg	4 m
41230	Belt	1,93	10	0.69	3.45	2.49	48	48m	approx.	3.17	14	4.5 m

strap	m × 0,69 m	m	m	m	mm	m / 42m m	3.450 mm × approx. 690 mm × approx. 155 mm	m	.1 kg
-------	------------------	---	---	---	----	-----------------	---	---	----------

Seventec RC S

Details

The ladder for optimal safety in outdoor areas.

- 85 mm deep treads with perforation to allow liquids to flow off and profiling to ensure stability.
- Large safety platform (380 x 260 mm) with integrated hinged connection.
- Reflective strips on the stiles to improve visibility in poor visual conditions.
- Optimal stability thanks to the fold-down locking bar on both sides.
- Practical tray with plenty of space for tools and small items.
- Two integrated bucket hooks.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Smooth external stile surfaces that are comfortable to hold.
- Treads and stiles made from extruded aluminium sections.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty 10 years

Standards EN 131 professional

Platform width 380 mm

Material Aluminium

Platform length 260 mm

Anti splay Rigid locking bar

Coating natural

Connection Stile-Rung riveted

Tread depth 85 mm

Load max. 150 kg

Tray Aluminium

Pitch rung/tread 218 mm

Producttype Riveted stepladder with treads

Type rung/tread RC tread

Stile depth 87 mm

Stile depth 87 mm

Variants

Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Vertical ladder height	Weight	Working height
40493	0,71 m × 0,45 m	3	0.45 m	1.44 m	0.7 m	1.450 mm × 460 mm × 250 mm	1.31 m	6.3 kg	2.7 m
40494	0,88 m × 0,48 m	4	0.47 m	1.67 m	0.9 m	1.680 mm × 490 mm × 250 mm	1.54 m	7.9 kg	2.9 m
40495	1,05 m × 0,5 m	5	0.49 m	1.9 m	1.1 m	1.910 mm × 510 mm × 250 mm	1.79 m	8.1 kg	3.1 m

Seventec S

Details

High stability, comfortable ascent and descent due to deep treads and smooth external stile surfaces that are comfortable to grip.

- Treads 85 mm deep for safe standing.
- Large safety platform (380 x 260 mm) with integrated hinged connection.
- Optimal stability thanks to the fold-down locking bar on both sides.
- Practical tray with plenty of space for tools and small items.
- Two integrated bucket hooks.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Smooth external stile surfaces that are comfortable to hold.
- Treads and stiles made from extruded aluminium sections.

Hints and special features

- Complies with EN 131 Professional.

More Information	
Warranty	10 years
Standards	EN 131 professional
Platform width	380 mm
Material	Aluminium

Platform length	260 mm
Anti splay	Rigid locking bar
Coating	natural
Connection Stile-Rung	riveted
Tread depth	85 mm
Load	max. 150 kg
Tray	Aluminium
Pitch rung/tread	218 mm
Producttype	Riveted stepladder with treads
Type rung/tread	serrated
Stile depth	87 mm
Stile depth	87 mm

Variants

Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Vertical ladder height	Weight	Working height
40333	0,73 m × 0,45 m	3	0.45 m	1.44 m	0.7 m	1.450 mm × 460 mm × 250 mm	1.33 m	6 kg	2.7 m
40334	0,88 m × 0,47 m	4	0.47 m	1.67 m	0.9 m	1.680 mm × 490 mm × 250 mm	1.54 m	7 kg	2.9 m
40335	1,04 m × 0,49 m	5	0.49 m	1.9 m	1.1 m	1.910 mm × 510 mm × 250 mm	1.76 m	8 kg	3.1 m
40336	1,19 m × 0,51 m	6	0.52 m	2.13 m	1.35 m	2.140 mm × 530 mm × 250 mm	1.97 m	9 kg	3.35 m
40337	1,35 m × 0,54 m	7	0.54 m	2.35 m	1.55 m	2.360 mm × 560 mm × 250 mm	2.19 m	10.5 kg	3.55 m
40338	1,51 m × 0,56 m	8	0.56 m	2.6 m	1.75 m	2.590 mm × 570 mm × 250 mm	2.41 m	13 kg	3.75 m

40340	1,82 m × 0,6 m	10	0.61 m	3.05 m	2.2 m	3.050 mm × 630 mm × 250 mm	2.82 m	14 kg	4.2 m
-------	-------------------------	----	--------	--------	-------	----------------------------------	--------	-------	-------

Nova S

Details

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

- 80 mm deep surfaces to stand on.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- Strong Perlon rung hooks and rung locking mechanism, from 7 rungs.
- Patented tread construction: robust, stable, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.

Hints and special features

- Complies with EN 131 Professional.

More Information	
Warranty	10 years
Standards	EN 131 professional
Platform width	250 mm
Material	Aluminium
Platform length	250 mm
Anti splay	Belt strap
Coating	natural
Connection Stile-Rung	flanged
Tread depth	80 mm
Load	max. 150 kg
Tray	Plastic
Pitch rung/tread	216 mm
Producttype	Stepladder with flanged treads
Type rung/tread	serrated
Stile depth	48 mm
Stile depth	48 mm

Variants

Order number	Anti splay	Base	Numb er of rungs, incl. platfor m	Overall base width	Overall length	Platform height	Transp ort dimen sions	Vertical ladder height	Weight	Wo rkin g hei ght
42453		0,69 m × 0,42 m	3	0.42 m	1.34 m	0.61 m	1.350 mm × 420 mm × 120 mm	1.22 m	4.8 kg	2.6 m
42454		0,84 m × 0,44 m	4	0.44 m	1.57 m	0.83 m	1.580 mm × 440 mm × 120 mm	1.43 m	5.8 kg	2.8 5 m
42455		0,99 m × 0,46 m	5	0.46 m	1.8 m	1.05 m	1.810 mm × 470 mm × 120 mm	1.65 m	6.9 kg	3.0 5 m
42456		1,14 m × 0,49 m	6	0.49 m	2.03 m	1.26 m	2.060 mm × 490 mm × 120 mm	1.86 m	8 kg	3.2 5 m
42457	Belt strap	1,28 m × 0,51 m	7	0.51 m	2.26 m	1.48 m	2.270 mm × 520 mm × 120 mm	2.08 m	9.1 kg	3.5 m
42458	Belt strap	1,44 m × 0,54 m	8	0.54 m	2.49 m	1.7 m	2.500 mm × 540 mm × 120 mm	2.29 m	10.2 kg	3.7 m

Scana S

Details

High degree of comfort while working due to abrasion-resistant, anodised stiles and large storage tray.

- Tread depth 80 mm.
- Abrasion-resistant, anodised stiles.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- High-strength Perlon belts prevent splay from 6 rungs.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.

Hints and special features

- Complies with EN 131 Professional.

More Information	
Warranty	10 years
Standards	EN 131 professional
Platform width	250 mm
Material	Aluminium
Platform length	250 mm
Anti splay	Belt strap
Coating	anodised
Connection Stile-Rung	riveted
Tread depth	80 mm
Load	max. 150 kg
Tray	Plastic
Pitch rung/tread	216 mm
Producttype	Riveted stepladder with treads
Type rung/tread	serrated
Stile depth	40 mm
Stile depth	40 mm

Variants

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Vertical ladder height	Weight	Working height
44153		0,67 m × 0,41	3	0.41 m	1.36 m	0.59 m	1.370 mm × 410 mm	1.2 m	3.7	2.6

		m					× 110 mm		kg	m
44154		0,82 m × 0,43 m	4	0.43 m	1.59 m	0.81 m	1.600 mm × 440 mm × 110 mm	1.42 m	4.4 kg	2.8 m
44155		0,96 m × 0,46 m	5	0.46 m	1.82 m	1.03 m	1.830 mm × 460 mm × 110 mm	1.64 m	5.1 kg	3 m
44156	Belt strap	1,1 m × 0,48 m	6	0.48 m	2.05 m	1.24 m	2.060 mm × 490 mm × 110 mm	1.85 m	5.9 kg	3.25 m
44157	Belt strap	1,25 m × 0,51 m	7	0.51 m	2.29 m	1.47 m	2.290 mm × 510 mm × 110 mm	2.08 m	6.6 kg	3.5 m
44158	Belt strap	1,7 m × 0,53 m	8	0.53 m	2.52 m	1.7 m	2.520 mm × 530 mm × 110 mm	2.31 m	8 kg	3.7 m

EFAmix S

Details

The special ladders for all applications in electrical environments.

- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Treads made from extruded aluminium section.

Hints and special features

- Complies with EN 131 Professional.

More Information

Warranty10 years

StandardsEN 131 professional

Platform width	250 mm
Material	Aluminium / plastic
Platform length	250 mm
Anti splay	Belt strap
Connection Stile-Rung	flanged
Tread depth	80 mm
Load	max. 150 kg
Tray	Plastic
Pitch rung/tread	230 mm
Producttype	GRP composite stepladder with treads
Type rung/tread	serrated
Stile depth	50 mm
Stile depth	50 mm

Variants

Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weight	Working height
40431	0,75 m × 0,52 m	3	0.52 m	1.4 m	0.68 m	1.390 mm × approx. 520 mm × 100 mm	6 kg	2.7 m
40432	0,91 m × 0,55 m	4	0.55 m	1.65 m	0.91 m	1.640 mm × approx. 550 mm × 100 mm	7 kg	2.9 m
40433	1,07 m × 0,57 m	5	0.57 m	1.9 m	1.14 m	1.890 mm × approx. 570 mm × 100 mm	8 kg	3.15 m
40434	1,24 m × 0,6 m	6	0.6 m	2.15 m	1.37 m	2.140 mm × approx. 600 mm × 100 mm	9 kg	3.35 m
40435	1,4 m × 0,62 m	7	0.62 m	2.4 m	1.6 m	2.390 mm × approx. 620 mm × 100 mm	10 kg	3.6 m

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru