

Алматы (7273)495-231

Ангарск (3955)60-70-56

Архангельск (8182)63-90-72

Астрахань (8512)99-46-04

Барнаул (3852)73-04-60

Белгород (4722)40-23-64

Благовещенск (4162)22-76-07

Брянск (4832)59-03-52

Владивосток (423)249-28-31

Владикавказ (8672)28-90-48

Владимир (4922)49-43-18

Волгоград (844)278-03-48

Вологда (8172)26-41-59

Воронеж (473)204-51-73

Екатеринбург (343)384-55-89

Иваново (4932)77-34-06

Ижевск (3412)26-03-58

Иркутск (395)279-98-46

Казань (843)206-01-48

Калининград (4012)72-03-81

Калуга (4842)92-23-67

Кемерово (3842)65-04-62

Киров (8332)68-02-04

Коломна (4966)23-41-49

Кострома (4942)77-07-48

Краснодар (861)203-40-90

Красноярск (391)204-63-61

Курск (4712)77-13-04

Курган (3522)50-90-47

Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13

Москва (495)268-04-70

Мурманск (8152)59-64-93

Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12

Новокузнецк (3843)20-46-81

Ноябрьск (3496)41-32-12

Новосибирск (383)227-86-73

Омск (3812)21-46-40

Орел (4862)44-53-42

Оренбург (3532)37-68-04

Пенза (8412)22-31-16

Петрозаводск (8142)55-98-37

Псков (8112)59-10-37

Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15

Рязань (4912)46-61-64

Самара (846)206-03-16

Санкт-Петербург (812)309-46-40

Саратов (845)249-38-78

Севастополь (8692)22-31-93

Саранск (8342)22-96-24

Симферополь (3652)67-13-56

Смоленск (4812)29-41-54

Сочи (862)225-72-31

Ставрополь (8652)20-65-13

Сургут (3462)77-98-35

Сыктывкар (8212)25-95-17

Тамбов (4752)50-40-97

Тверь (4822)63-31-35

Тольятти (8482)63-91-07

Томск (3822)98-41-53

Тула (4872)33-79-87

Тюмень (3452)66-21-18

Ульяновск (8422)24-23-59

Улан-Удэ (3012)59-97-51

Уфа (347)229-48-12

Хабаровск (4212)92-98-04

Чебоксары (8352)28-53-07

Челябинск (351)202-03-61

Череповец (8202)49-02-64

Чита (3022)38-34-83

Якутск (4112)23-90-97

Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru

Skymaster Plus X

One ladder, many functions: the flexible solution for accessing higher places safely and providing extra stability. The ladder is particularly safe and comfortable to use due to the 80 mm deep treads on the upper ladder.

Product description

- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- Upper ladder with top wheel assembly.
- Upper ladder can also be used separately as single ladders for Order Nos. 41578-41579.
- Maximum stability thanks to rigid connection on both sides.
- Strong Perlon straps.
- The horizontal stabiliser bar is fitted with castors for ergonomic transport.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Product features

Coating: natural
Connection Stile-Rung: flanged
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 265 mm
Producttype: Flanged multi-function ladder, 3-section
Rigid locking bar: on both sides
Standards: EN 131 professional
Type rung/tread: serrated
Warranty: 10 years
Wheels: Rubber
adjustable-height-pf: 0

Product variants

Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions
41578	5.81 m	4.13 m	8	3 × 8	2.45 m	73 mm	approx. 2.450 mm × approx. 500 mm × approx. 220 mm
41579	6.88 m	4.94 m	10	3 × 10	3.01 m	85 mm	approx. 3.015 mm × approx. 500 mm × approx. 230 mm
41580	8.61 m	6.1 m	12	3 × 12	3.58 m	98 mm	approx. 3.585 mm × approx. 500 mm × approx. 245 mm
41581	9.73 m	6.94 m	14	3 × 14	4.14 m	98 mm	approx. 4.145 mm × approx.



Hints and special features

Optimum stability due to extra-wide horizontal stabiliser bar and two rigid locking bars.
Complies with EN 131 Professional.



ZARGES

Skymaster X

Convertible to take on challenging tasks with greater safety.

Product description

- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Product features

Coating: natural
Connection Stile-Rung: flanged
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 265 mm
Producttype: Flanged multi-function ladder, 3-section
Rigid locking bar: on one side
Standards: EN 131 professional
Tread depth: 30 mm
Type rung/tread: serrated
Warranty: 10 years
adjustable-height-pf: 1

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions
41536	4.1 m	3 m	6	3 × 6	1.9 m	68 mm	1.880 mm × 500 mm × 180 mm
41537	5 m	3.6 m	7	3 × 7	2.2 m	68 mm	2.160 mm × 500 mm × 180 mm
41538	5.8 m	4.1 m	8	3 × 8	2.45 m	73 mm	2.440 mm × 500 mm × 200 mm
41539	6.7 m	4.7 m	9	3 × 9	2.7 m	85 mm	2.730 mm × 500 mm × 200 mm
41540	6.9 m	4.95 m	10	3 × 10	3 m	85 mm	3.010 mm × 500 mm × 210 mm
41542	8.6 m	6.1 m	12	3 × 12	3.55 m	98 mm	3.590 mm × 500 mm × 230 mm
41544	9.7 m	6.95 m	14	3 × 14	4.15 m	98 mm	4.140 mm × 500 mm ×



ZARGES

Skymaster DX

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

Product description

- Robust extruded-section triangular rungs with step horizontal in working position.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.

Product features

Coating: natural
Connection Stile-Rung: flanged
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 265 mm
Producttype: Flanged multi-function ladder, 3-section
Standards: EN 131 professional
Tread depth: 38 mm
Type rung/tread: serrated
Warranty: 10 years
adjustable-height-pf: 1

Product variants

Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions
44837	4.4 m	3.25 m	7	3 × 7	2.14 m	58 mm	2.130 mm × 500 mm × 170 mm
44838	5.25 m	3.85 m	8	3 × 8	2.42 m	68 mm	2.410 mm × 500 mm × 170 mm
44839	6.1 m	4.4 m	9	3 × 9	2.7 m	73 mm	2.690 mm × 500 mm × 190 mm
44840	6.65 m	4.65 m	10	3 × 10	2.98 m	73 mm	2.970 mm × 500 mm × 190 mm
44841	7.2 m	5.25 m	11	3 × 11	3.26 m	85 mm	3.270 mm × 500 mm × 200 mm
44842	8.3 m	5.8 m	12	3 × 12	3.54 m	85 mm	3.550 mm × 500 mm × 220 mm
44844	9.45 m	6.654 m	14	3 × 14	4.1 m	98 mm	4.110 mm × 500 mm × 220 mm



Hints and special features

Complies with EN 131 Professional.



ZARGES

Multimax M

Versatile ladder with up to four functions which folds to extremely small dimensions for transport.

Product description

- Easy-to-use, automatically engaging aluminium safety hinge.
- Order no. 41610 and 41611 with a foldable wooden board for use as a work platform.
- Ladder width: 420 mm.
- Compact for transport, does not take up a lot of space when folded.
- High strength, non-twist rung/stile connections.
- Extra-wide crosspiece.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Height as work platform: 0.99 m
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged multipurpose ladder, 4-section
 Tread depth: 30 mm
 Type rung/tread: serrated
 Warranty: 10 years



Hints and special features

Order Nos. 41688 and 41689 cannot be used as a work trestle and single ladder with wall support.
 Folds to a compact size for transport and storage.

Product variants

Order number	Dimensions, folded	Length	Length as lean-to ladder	Length as stepladder	Length as work platform	Number of rungs	Number of rungs
41610	1 m × 0,8 m × 0,28 m	1 m	3,65 m	1,76 m	1,4 m	3	4 × 3
41611	1,21 m × 0,9 m × 0,28 m	1,21 m	4,16 m	2 m	1,96 m	3	2 × 3 + 2 × 4
41688	1,25 m × 0,9 m × 0,28 m	1,25 m	4,75 m	2,29 m		4	4 × 4
41689	1,56 m × 1,1 m × 0,28 m	1,56 m	5,85 m	2,84 m		5	4 × 5

Order number	Overall base width	Stile depth	Transport dimensions	Weight	Width	Working height	adjustable-height-pf
41610	0.8 m	58 mm	1.000 mm × 420 mm × 280 mm	18.2 kg	0.8 m	4,45 m	0
41611	0.9 m	58 mm	1.210 mm × 420 mm × 280 mm	20.6 kg	0.9 m	5 m	0
41688	0.9 m	58 mm	1.250 mm × 420 mm × 280 mm	16 kg	0.9 m	5,5 m	
41689	1.1 m	59 mm	1.560 mm × 420 mm × 280 mm	20 kg	1.1 m	6,55 m	



ZARGES

Multitec M

The compact version for a wide range of uses and with a good price/performance ratio.

Product description

- Can be used as a single ladder, a stepladder with double-sided access or as a practical work platform.
- Order no. 42377-42379 with a folding wooden board for use as a work platform.
- Order Nos. 42377 - 42379 are equipped with two horizontal stabiliser bars, Order No. 42384 with one horizontal stabiliser bar.
- External width of ladder body: 350 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged multipurpose ladder, 4-section
 Tread depth: 30 mm
 Type rung/tread: serrated
 Warranty: 10 years

Hints and special features

Order No. 42384 may not be used as a work platform or a single ladder with wall support.

Product variants

Order number	Dimensions, folded	Height as work platform	Length	Length as lean-to ladder	Length as stepladder	Length as work platform	Number of rungs
42377	1,02 m × 0,75 m × 0,26 m	0.99 m	1.02 m	3.62 m	1.85 m	1.55 m	3
42378	1,22 m × 0,8 m × 0,26 m	0.99 m	1.22 m	4.19 m	2.13 m	2.11 m	3
42384	1,3 m × 0,9 m × 0,26 m		1.3 m	4.74 m	2.41 m		4
42379	1,5 m × 0,9 m × 0,26 m	0.99 m	1.5 m	4.74 m	2.41 m	2.67 m	3

Order number	Number of rungs	Overall base width	Stile depth	Transport dimensions	Vertical ladder height	Weight	Width
42377	4 × 3	0.75 m	59 mm	1.030 mm × 360 mm × 270 mm	1.75 m	16.2 kg	0.75 m
42378	2 × 3 + 2 × 4	0.8 m	59 mm	1.230 mm × 350 mm × 270 mm	2 m	19 kg	0.8 m
42384	4 × 4	0.9 m	59 mm	1.310 mm × 360 mm × 270 mm	2.3 m	15.5 kg	0.9 m
42379	2 × 3 + 2 × 5	0.9 m	61 mm	1.510 mm × 350 mm × 270 mm	2.3 m	22.2 kg	0.9 m



Variomax V

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

Product description

- Easy-to-use, automatically engaging aluminium safety hinge.
- Safe height adjustment thanks to four pull handles of diecast aluminium.
- Single ladder, stepladder and staircase stepladder in one.
- Fitted with fold-out stabilisers to allow the product to be used as a single ladder in compliance EN131-1 (except for the 4x3 model).
- The stabilisers can be folded in to save space during transport or when the product is used as a stepladder.
- Rung by rung working height adjustment in all versions.
- Quickly and easily converts from one mode to another.
- High strength, non-twist rung/stile connections.



Product features

Coating: natural

Connection Stile-Rung: flanged

Load: max. 150 kg

Material: Aluminium

Pitch rung/tread: 265 mm

Producttype: Flanged telescopic multi-function ladder, 4-section

Tread depth: 30 mm

Type rung/tread: serrated

Warranty: 10 years

adjustable-height-pf: 1

Product variants

Order number	Dimensions, folded	Length	Length as lean-to ladder	Length as trestle	Number of rungs	Number of rungs	Transport dimensions
41934	0,97 m × 0,5 m × 0,21 m	0.97 m	2.97 m	1.45 m	3	4 × 3	970 mm × 500 mm × 210 mm
41383	1,3 m × 0,64 m × 0,21 m	1.3 m	4.2 m	2 m	4	4 × 4	1.310 mm × approx. 640 mm × 210 mm
41384	1,58 m × 0,71 m × 0,21 m	1.58 m	5.3 m	2.54 m	5	4 × 5	1.580 mm × approx. 710 mm × 210 mm
41385	1,86 m × 0,78 m × 0,21 m	1.86 m	6.4 m	3.1 m	6	4 × 6	1.860 mm × approx. 780 mm × 210 mm



ZARGES

Variotec V

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

Product description

- Required working height can be set in increments corresponding to the rung spacing.
- Folds down to a space-saving compact size for transport.
- Functional robust steel hinges, bolted and easy to replace.
- Fitted with fold-out stabilisers to allow the product to be used as a single ladder in compliance with EN131-1.
- The stabilisers can be folded in to save space during transport or when the product is used as a stepladder.
- Stiles made from extruded aluminium sections for maximum stability.
- High strength, non-twist rung/stile connections.



Hints and special features

Ideal for use on steps/stairs as a result of rung-by-rung height adjustment on both sides.

Product features

Coating: natural
Connection Stile-Rung: flanged
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 265 mm
Producttype: Flanged telescopic multi-function ladder, 4-section
Stile depth: 60 mm
Stile depth: 70 mm
Stile depth: 60mm / 70mm
Tread depth: 30 mm
Type rung/tread: serrated
Warranty: 10 years
adjustable-height-pf: 1

Product variants

Order number	Dimensions, folded	Length	Length as lean-to ladder	Length as trestle	Number of rungs	Number of rungs	Transport dimensions
42437	1,3 m × 0,64 m × 0,21 m	1.3 m	4.17 m	2.2 m	4	4 × 4	1.310 mm × approx. 640 mm × 200 mm
42438	1,58 m × 0,71 m × 0,21 m	1.58 m	5.29 m	2.7 m	5	4 × 5	1.580 mm × approx. 710 mm × 200 mm
42439	1,86 m × 0,78 m × 0,21 m	1.86 m	6.4 m	3.09 m	6	4 × 6	1.860 mm × approx. 780 mm × 210 mm

Combimaster X

Practical dual-function ladder that can be used as a single ladder or stepladder for flexible application.

Product description

- Can be used as either a single ladder or a stepladder.
- Strong, steel joint bolted to the stiles.
- Self-locking.
- One ladder section with broad horizontal stabiliser bar.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.

Product features

Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged multi-function folding ladder, 2-section
 Stile depth: 58 mm
 Tread depth: 30 mm
 Type rung/tread: serrated
 Warranty: 10 years
 adjustable-height-pf: 0



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Length as lean-to ladder	Length as stepladder	Number of rungs	Number of rungs	Transport dimensions	Weight	Wide crosspiece
41941	2.5 m	1.3 m	4	2 × 4	1.265 mm × 360 mm × 130 mm	6 kg	0.75 m
41942	3.6 m	1.85 m	6	2 × 6	1.870 mm × 360 mm × 130 mm	8 kg	0.8 m
41943	4.7 m	2.4 m	8	2 × 8	2.410 mm × 360 mm × 130 mm	12 kg	0.9 m

Vario B

Multi-function ladder that can be used on steps/stairs, with pull-out function for safe standing at great heights.

Product description

- Ideal for working on stairs, in sports halls, halls, etc.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Locks safely by means of hooks with lift-off retainer.
- 2 sturdy horizontal stabiliser bars provide a wide standing base.
- High strength, non-twist rung/stile connections.
- Sturdy bolt-on fittings made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged stepladder with rungs, height-adjustable
 Tread depth: 30 mm
 Type rung/tread: serrated
 Warranty: 10 years
 adjustable-height-pf: 1

Hints and special features

Ideal for use on steps/stairs as a result of rung-by-rung height adjustment on both sides.
 Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Overall span	Stile depth	Transport dimensions
41322	8	4 × 8	4.05 m	2.4 m	2.3 m	58 mm	2.387 mm × 426 mm × 258 mm
41323	10	4 × 10	4.95 m	3.01 m	2.7 m	73 mm	2.997 mm × 426 mm × 306 mm
41324	12	4 × 12	6.05 m	3.57 m	3.3 m	73 mm	3.569 mm × 426 mm × 306 mm



ZARGES

Varioflex B

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

Product description

- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Product features

Additional adjustment range on ladder section: 0.4 m

Coating: natural

Connection Stile-Rung: flanged

Load: max. 150 kg

Material: Aluminium

Pitch rung/tread: 265 mm

Producttype: Flanged stepladder with rungs and extendable stiles.

Tread depth: 30 mm

Type rung/tread: serrated

Warranty: 10 years

adjustable-height-pf: 1



Hints and special features

Ideal for applications in difficult terrain.
Complies with EN 131 Professional.

Product variants

Order number	Additional adjustment range on support section	Length excluding extension	Number of rungs	Number of rungs	Transport dimensions	Weight	Working height
41936	1.3 m	1.8 m	6	2 × 6	1.850 mm × 600 mm × 140 mm	12.5 kg	3 m
41938	1.85 m	2.35 m	8	2 × 8	2.410 mm × 650 mm × 140 mm	15.5 kg	3.55 m



ZARGES

Combimaster Plus X

Two ladders in one: combined stepladder and push-up ladder for safe standing.

Product description

- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.

Product features

Coating: natural

Connection Stile-Rung: flanged

Load: max. 150 kg

Material: Aluminium

Pitch rung/tread: 265 mm

Producttype: Flanged multi-function ladder, 2-section

Standards: EN 131 professional

Tread depth: 30 mm

Type rung/tread: serrated

Warranty: 10 years

adjustable-height-pf: 1



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Length as trestle	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions
42566	1.75 m	6	2 × 6	2.98 m	1.86 m	58 mm	1.860 mm × 420 mm × 125 mm
42568	2.27 m	8	2 × 8	4.1 m	2.42 m	58 mm	2.420 mm × 420 mm × 125 mm
42570	2.8 m	10	2 × 10	4.94 m	2.98 m	58 mm	2.980 mm × 420 mm × 125 mm
42572	3.33 m	12	2 × 12	6.06 m	3.54 m	73 mm	3.540 mm × 420 mm × 135 mm
42574	3.86 m	14	2 × 14	7.19 m	4.1 m	85 mm	4.110 mm × 420 mm × 140 mm
42576	4.39 m	16	2 × 16	8.31 m	4.67 m	98 mm	4.670 mm × 420 mm × 150 mm



ZARGES

Combimaster DX

The inexpensive alternative for universal use as a push-up ladder and stepladder.

Product description

- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- Robust extruded-section triangular rungs with step horizontal in working position.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Base: 1,64 m × 0,89 m

Coating: natural

Connection Stile-Rung: flanged

Load: max. 150 kg

Material: Aluminium

Pitch rung/tread: 265 mm

Producttype: Flanged multi-function ladder, 2-section

Standards: EN 131 professional

Tread depth: 38 mm

Type rung/tread: serrated

Warranty: 10 years

adjustable-height-pf: 1

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Length as trestle	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions
44868	2.25 m	8	2 × 8	3.82 m	2.4 m	58 mm	2.400 mm × 420 mm × 120 mm
44870	2.81 m	10	2 × 10	4.94 m	2.98 m	68 mm	2.970 mm × 430 mm × 120 mm
44872	3.33 m	12	2 × 12	6.06 m	3.54 m	73 mm	3.530 mm × 430 mm × 130 mm
44874	3.86 m	14	2 × 14	6.9 m	4.1 m	85 mm	4.090 mm × 430 mm × 135 mm



ZARGES

Telescopic combination ladder

Out of the boot and up: miniature format for transport, flexible use as a single ladder and stepladder.

Product description

- When pushed together, the ladder fits into any luggage compartment.
- Can only be used as a single ladder or a stepladder when fully extended.
- Wide treads ensure comfort when ascending and descending.
- Abrasion-resistant, anodised stiles.
- Original TELESTEPS with the proven AUTOSTEPS mechanism.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131-6.

Product features

Coating: anodised
Load: max. 150 kg
Pitch rung/tread: 300 mm
Standards: EN 131-6
Tread depth: 90 mm
Type rung/tread: serrated
Warranty: 10 years

Product variants

Order number	Number of treads	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece	Working height
41114	6 + 2	2.3 m	0.71 m	710 mm × 590 mm × 160 mm	14.5 kg	0.69 m	3.6 m
41115	8 + 2	3 m	0.78 m	800 mm × 600 mm × 170 mm	20 kg	0.77 m	4.2 m

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Волгодз (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Россия +7(495)268-04-70

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zarges.nt-rt.ru/> || zsc@nt-rt.ru